

MF2607H

(F.O.B. PORT OF ENTRY)



MASSEY FERGUSON®

TRACTOR FEATURES

ENGINE SYSTEM

- Simpson 2.6L, T4 Final, EPA & CARB Certified
- 3 Cylinder
- Turbocharged, Intercooled, HPCR Fuel Injection
- 74 (54.4 kW) PS Gross Engine Horsepower @ 2000 RPM
- 64 (47 kW) PTO Horsepower @ 2000 RPM with Independent PTO

FRONT AXLE - Two Factory Options

- 2 Wheel Drive with Telescopic Adjustment OR
- 4 Wheel Drive with Planetary Reduction Final Drives

POWER TRAIN

- Transmission - 8x8 Synchro Shuttle with ComfiMesh™ - Transmission Shift Control Lever on Right Side and Range Box Shift Control Lever on Left Side
- Mechanical F-R Shuttle Lever Left Side of Steering Wheel
- Outboard Planetary Final Drives
- Brakes - Internal Multi Wet Disc with Mechanical Actuation
- Parking Brake - Mechanical Hand Lever

PTO

- Independent PTO, 540 RPM, 6 Spline Shaft with Lever Operated Split Torque Clutch

THREE POINT LINKAGE

- Extendable Lower Links with Right Side Turnbuckle Adjustment - Category I/II Cross Drilled Ball Ends
- Sway Chain Stabilizers

HYDRAULICS

- Hydrostatic Steering with Separate Reservoir
- Ferguson 3-Point Hitch System
- 3-Point Hitch Pump Flow (4.2 GPM) *
- Draft, Position and Response Control
- 2 Spool Valves Included
- Hydraulic Pump Flow 11.2 GPM at Rear Remote *
- Maximum Hydraulic Flow 15.7 GPM (59.5 LPM) (Steering, 3-Point and Auxiliary Combined)

ELECTRICAL

- Headlights
- Single Rear Work Light
- Safety Lights
- 7 Pin ASAE Outlet

OPERATORS ENVIRONMENT

- Straddle Mount
- Grammar Seat that Inclines as it Moves Rearward
- Retractable Seatbelt
- Folding ROPS
- Suspended Foot Pedals
- Ground-Level Fuel Tank

OTHER STANDARD FEATURES

- Tilting One Piece Hood
- Swinging Drawbar
- Tool Box
- Drawbar Clevis

*Manufacturer's Estimate

LOADER FEATURES

MF FLx2815 Pin Type Style Loader

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.76 inch Double Acting Lift Cylinders
- (2) 2.56 inch Double Acting Bucket Cylinders
- Hydraulic Valves with Integrated Joystick Mount to Right Side Loader Subframe
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- 72-inch Standard Duty Skid Steer Bucket
- **Fits all MF2600H Series 2wd Tractors**
- Maximum Lift Height: 111 Inches at Pivot Pin
- Lift Capacity to Full Height at Pivot Pin: 2,810 lbs
- Breakout Force: 4,240 lbs at Pivot Pin
- Rated Hydraulic Pressure: 2350 PSI
- Grille Guard Standard

MF911X Loader

- One Piece Main Frame with Tapered Arms and Single Cross Member
- Quick Attach Loader Frame Mount with Pin Lock
- Built-in Parking Stands
- (2) 2.4 inch Double Acting Lift Cylinders
- (2) 2.4 inch Double Acting Bucket Cylinders
- Hydraulic Valves with Integrated Joystick Mount to Right Side Loader Subframe
- Hydraulic Lines Routed Inside Main Frame for Protection and Visibility
- Galvanized Steel Bushings with Recessed Grease Points
- Universal Skid Steer or Euro Hook Type Implement Attachments
- **Fits all MF2600H Series 4wd Tractors**
- Maximum Lift Height: 115 inches at Pivot
- Lift Capacity to Full Height at 31.5 inches Forward of Pivot Pin: 1510 lbs
- Breakout Force: 2750 lbs
- Rated Hydraulic Pressure: 2755 PS
- Grille Guard Standard